CSC2/455 Software Analysis and Improvement Partial Redundancy Elimination

Sreepathi Pai

URCS

February 25, 2019

Outline

Review

Partial Redundancy Elimination

Postscript



Outline

Review

Partial Redundancy Elimination

Postscript

◆□> ◆□> ◆□> ◆□> ○□

Optimizations: Dead Code Elimination

Find useful operations (backward analysis)

- Find useful conditional branches
 - Reverse Dominance Frontier
- Remove code, and "touch up CFG"


Outline


Review

Partial Redundancy Elimination

Postscript


Redundancy: Fully Redundant







◆□▶ ◆□▶ ◆臣▶ ◆臣▶ 臣 のへで

Redundancy: Loop Invariant




Redundancy: Partial Redundancy





◆□▶ ◆□▶ ◆臣▶ ◆臣▶ 臣 の�?


Eliminating Redundancy: Complication 1



(日) (四) (문) (문) (문)

Can we insert t = b + c in B_3 ?


Splitting Critical Edges



◆□▶ ◆舂▶ ◆注≯ ◆注≯ □注□


(Similar to when we were inserting minimal ϕ -functions.)

Eliminating Redundancy: Complication 2



Note that there is no block where t = b + c can be introduced without introducing computations not in the original program.

CFG duplication



(中) (문) (문) (문) (문)

(Possibility of exponential blowup.)

The Lazy Code Motion Algorithm

- Eliminate all expressions when it will not duplicate code
- Do not perform computations not in original program
 - Although where the computation is performed can change

- Delay computation for as long as possible
 - "Lazy"
 - Helps lower resource (esp. register) usage

Setup

For all blocks *B* in CFG, compute:

- e_use_B: set of expressions used in a block
- ▶ *e_kill*_B: set of expressions killed in block
 - usually by redefining subcomponents

Also, split all critical edges, inserting empty blocks.

◆□> ◆舂> ◆注> ◆注> 注目

Anticipable Expressions

Recall very busy expressions. An expression e is anticipable at at block p if:





Recall very busy expressions. An expression e is anticipable at at block p if:

- e is used/computed on all paths leading out of p
- And it is not killed before the use
- Implies that p can compute e and all paths could use this result

Anticipable Expressions Analysis

- Direction: Backwards
- Values: Expressions in programs
- ► Meet: ∩
- Transfer Function

•
$$f_B(x) = e_{-}use_B \cup (x - e_{-}kill_B)$$

Equations:

$$OUT[B] = \wedge_{S \in succ(B)} IN[S]$$

◆□▶ ◆□▶ ◆三▶ ◆三▶ 三三 のへで

 $\blacktriangleright \text{ IN}[B] = f_B(\text{OUT}[B])$

$$\blacktriangleright$$
 $\top = U$

$$\blacktriangleright \text{ IN}[EXIT] = \emptyset$$

Available Expressions

An expression is available at a program point p if:

- it has been computed along all paths leading into p
- it has not been killed since being computed until p
- (NEW) it is anticipated at p
 - we could make it available if it is anticipated

Available Expressions Analysis

- Direction: Forwards
- ► Meet: ∩
- Transfer function

• $f_B(x) = (e_u se_B \cup anticipable[B].in) \cup (x - e_kill_B)$

◆□▶ ◆□▶ ◆三▶ ◆三▶ 三三 のへで

Equations

•
$$\operatorname{IN}[B] = \wedge_{P \in pred(B)} \operatorname{OUT}[P]$$

• $OUT[B] = f_B(\operatorname{IN}[B])$

- \blacktriangleright $\top = U$
- $OUT[ENTRY] = \emptyset$

Positioning Expressions


- When is the earliest an expression can be evaluated?
- When is the latest an expression can be evaluated?

◆□▶ ◆□▶ ◆臣▶ ◆臣▶ 臣 のへで

Positioning Expressions: Earliest

When is the earliest an expression can be evaluated?
When it anticipated, but not available
earliest[B] = anticipable[B].in - available[B].in
Observe notation for results of different analyses

Anticipable + (Not) Available = Earliest



Positioning Expressions: Latest

- When is the latest an expression can be evaluated?
 - When it can no longer be postponed
- "Postponed": expression pushed down from earliest placement
 - When can we push down an expression into the next block?

An expression e is postponable to a block p if:

- e could be placed in block b before p (earliest is before p)
- Such that it is available on all paths leading to p from ENTRY

(日) (문) (문) (문) (문)

But e is not used after block b (and before p)

Postponable Expressions Analysis

- Direction: Forwards
- Values: Expressions
- ► Meet: ∩
- Transfer functions
 - $f_B(x) = (earliest[B] \cup x) e_use_B$


◆□▶ ◆□▶ ◆三▶ ◆三▶ 三三 のへで

- Equations
 - $\operatorname{OUT}[B] = f_B(\operatorname{IN}[B])$
 - $\blacktriangleright \text{ IN}[B] = \wedge_{P \in pred(B)} OUT[P]$

$$\blacktriangleright$$
 $\top = U$

• $OUT[ENTRY] = \emptyset$

Postponable



Postponement Frontier

A block p is on the postponement frontier for an expression e if

- e can be postponed to p
- e cannot be placed at entry to a successor s of p
 - e is used in p
 - e is not postponable from some predecessor of s
 - e is not in earliest[S]

$\begin{aligned} \textit{latest}[B] = & (\textit{earliest}[B] \cup \textit{postponable}[B].\textit{in}) \cap \\ & (e_{_}\textit{use}_B \cup (\cap_{S \in \textit{succ}(B)}(\textit{earliest}[S] \cup \textit{postponable}[S].\textit{in}))^\complement) \end{aligned}$

◆□▶ ◆□▶ ◆臣▶ ◆臣▶ 臣 の�?

(Note: A^{\complement} means the complement of set A)

An expression *e* in block *p* is used if:

- Some block *q* uses *e*
- There exists a path from p to q that does not invalidate e

◆□▶ ◆□▶ ◆三▶ ◆三▶ 三三 のへで

I.e. recompute e or invalidate its operands

Used Expressions Analysis

- Direction: Backwards
- Values: Expressions
- ► Meet: ∪
- Transfer function
 - $f_B(x) = (x \cup e_use_B) latest[B]$

◆□▶ ◆□▶ ◆臣▶ ◆臣▶ 臣 の�?

- Equations
 - $\blacktriangleright \text{ IN}[B] = f_B(\text{OUT}[B])$
 - $\blacktriangleright \text{ OUT}[B] = \wedge_{S \in succ(B)} \text{IN}[s]$

$$\blacktriangleright$$
 $\top = \emptyset$

 $\blacktriangleright \text{ IN}[EXIT] = \emptyset$

Putting it all together - I

Compute anticipable[B].in, available[B].in

- Compute earliest[B]
- Compute postponable[B].in
- Compute latest[B]
- Compute used[B].out

Putting it all together - II

For each expression x + y in program:


- Create t = x + y (where t is a unique temporary)
- Place t = x + y at the beginning of all blocks B such that
 - x + y is in *latest*[B] \cap *used*[B].*out*
 - i.e. B is the last block where x + y can be placed, and x + y is used after B

◆□▶ ◆□▶ ◆臣▶ ◆臣▶ 臣 の�?

- Replace all x + y with t in all block B where:
 - ▶ $x + y \in (e_u se_B \cap (latest[B]^{\complement} \cup used[B].out)$
 - I.e., x + y is in e_use_B, and
 - x + y is NOT in *latest*[B], or
 - x + y is in used[B].out

Algorithm 9.36 in the Dragon Book.

Final result



◆□▶ ◆□▶ ◆臣▶ ◆臣▶ 臣 の�?


Outline

Review

Partial Redundancy Elimination

Postscript

References



Section 9.5

