# Lecture 20: Introduction to Graphics and 3D Modeling

#### Yuhao Zhu

http://yuhaozhu.com yzhu@rochester.edu CSC 259/459, Fall 2025 Computer Imaging & Graphics

### The Roadmap

**Theoretical Preliminaries** 

**Human Visual Systems** 

Display and Camera

Modeling and Rendering

#### 3D Modeling

Rasterization and GPU
Ray Tracing
Shading












### Graphics Rendering



- Why do those images look "real" to you?
  - > Photorealism: a rendered image that looks like taken by a camera
- Simulating the camera pipeline (sometimes assuming perfect optical to electrical signal transformation)
  - Description Could simulate some desired optical distortions

### Computer Graphics




## Modeling Objects


### 3D Modeling


Parametric/Implicit surface

Polygon mesh

Point cloud










https://twitter.com/dmitriatsafe/status/1066037693174341632 https://commons.wikimedia.org/wiki/File:Sphere\_-\_monochrome\_simple.svg


### Mesh






### Mesh






https://en.wikipedia.org/wiki/Polygon\_mesh


### Normals





https://en.wikipedia.org/wiki/Normal\_(geometry)

### General Idea of Representing a Mesh



#### **Encoding the coordinates of each vertex**

V0 {1, 1, 2}, V1 {-1, 2, 1}, V2 {0, 1, 0}, V3 {-1, -1, 2}, V4 {1, -1, 2}

#### **Encoding vertices of each face**

{V0, V2, V1}, {V1, V2, V4, V3}

Could also have a normal vector list and various other primitives

#### RenderMan-like Interface

# of vertices in each face

Vertex Index Array


PointsPolygon [3, 4] [0, 2, 1, 1, 2, 4, 3] "P"

[1, 1, 2, -1, 2, 1, 0, 1, 0, -1, -1, 2, 1, -1, 2]

Vertex Coordinates Array


### Polygon Triangulation

- Converting a polygon into a set of triangles.
  - > Why? It usually allows more efficient implementations to have just one kind of primitive.



A "fan triangulation" that converts a convex N-gon into N-2 faces.

Ear-clipping triangulation.




https://en.wikipedia.org/wiki/Polygon\_triangulation

### Parametric Curve


▶ Parametric curve: defining a curve by evaluating a set of parametric equations. Each equation has 1 parameter.  $\mathbb{R} \rightarrow \mathbb{R}^2$ .

#### Parabola ( $y = x^2$ )



$$x = t$$
$$y = t^2$$


#### Ellipse $(x^2/a^2 + y^2/b^2 = 1)$



To define a curve, the parametric equations have 1 parameter (t).

### Parametric Surface


▶ Parametric surface: defining a surface by evaluating a set of parametric equations. Each equation have 2 parameters.  $\mathbb{R}^2 \to \mathbb{R}^3$ .




To define a surface, the parametric equations have 2 parameters.


- Dezier curve is a kind of parametric curve expressed as a weighted sum of a set of control points.
  - > Weights are given by the Bernstein polynomial. Two end control points are on the curve.


#### Linear Bezier curve





https://en.wikipedia.org/wiki/B%C3%A9zier\_curve





Quadratic bezier curve has 3 control points. The curve changes with the control points.

#### **Quadratic Bezier curve**


$$P_A = (1 - t) P_0 + t P_1$$
  
 $P_B = (1 - t) P_1 + t P_2$   
 $P = (1 - t) P_A + t P_B$ 


$$(1 - t)^2 + 2t(1-t) + t^2 = 1$$
. P is a weighted sum of P<sub>0</sub>, P<sub>1</sub>, P<sub>2</sub>.

$$P = (1 - t)^2 P_0 + 2t(1-t) P_1 + t^2 P_2$$


▶ A bezier curve of order n has (n+1) control points.

#### Third-order Bezier curve






$$P = (1 - t)^3 P_0 + 3(1 - t)^2 t P_1 + 3(1 - t)^2 t^2 P_2 + t^3 P_3$$




https://en.wikipedia.org/wiki/B%C3%A9zier\_curve


▶ A bezier curve of order n has (n+1) control points.


Third-order Bezier curve





#### Fourth-order Bezier curve





https://en.wikipedia.org/wiki/B%C3%A9zier\_curve


Weights. Sum of weights is 1. So any point is a weighted sum of all the control points.

$$B(t) = \sum_{i=0}^{n} b_{i,n}(t) P_i$$
Parameter

Basis functions:
Bernstein
polynomials

$$\longrightarrow b_{i,n}(t) = \binom{n}{t} t^i (1-t)^{n-i}$$

Binomial coefficients 
$$- \left( \begin{array}{c} n \\ t \end{array} \right) = \frac{n!}{t!(n-t)!}$$



The first and last control points are also the end points of the generate curve.


https://en.wikipedia.org/wiki/B%C3%A9zier\_curve

Control

### Bezier Surface

A (m, n) bezier surface defines a surface where every point is a weighted sum of  $(m+1) \times (n+1)$  control points.

A (3, 3) Bezier surface/patch



$$= B_0^3(u)B_0^3(v)P_{00} + B_1^3(u)B_0^3(v)P_{10} + B_2^3(u)B_0^3(v)P_{20} + B_3^3(u)B_0^3(v)P_{30}$$

$$+ B_2^3(v)B_2^3(v)P_{00} + B_3^3(v)B_2^3(v)P_{10} + B_2^3(v)B_3^3(v)P_{20} + B_3^3(v)B_3^3(v)P_{20}$$

$$+B_0^3(u)B_1^3(v)P_{01} + B_1^3(u)B_1^3(v)P_{11} + B_2^3(u)B_1^3(v)P_{21} + B_3^3(u)B_1^3(v)P_{31}$$

$$+B_0^3(u)B_2^3(v)P_{02}+B_1^3(u)B_2^3(v)P_{12}+B_2^3(u)B_2^3(v)P_{22}+B_3^3(u)B_2^3(v)P_{32}$$


$$+B_0^3(u)B_3^3(v)P_{03} + B_1^3(u)B_3^3(v)P_{13} + B_2^3(u)B_3^3(v)P_{23} + B_3^3(u)B_3^3(v)P_{33}$$


$$p(u,v) = \begin{bmatrix} (1-u)^3, \ 3u(1-u)^2, \ 3u^2(1-u), \ u^3 \end{bmatrix} \times \begin{bmatrix} P_{00} \ P_{01} \ P_{02} \ P_{03} \\ P_{10} \ P_{11} \ P_{12} \ P_{13} \\ P_{20} \ P_{21} \ P_{22} \ P_{23} \\ P_{30} \ P_{31} \ P_{32} \ P_{33} \end{bmatrix} \times \begin{bmatrix} (1-v)^3 \\ 3v(1-v)^2 \\ 3v^2(1-v) \\ v^3 \end{bmatrix}$$


### Bezier Surface

A (m, n) bezier surface defines a surface where every point is a weighted sum of  $(m+1) \times (n+1)$  control points.

A (3, 3) Bezier surface/patch







https://en.wikipedia.org/wiki/B%C3%A9zier\_curve


### Bezier Surface

A (m, n) bezier surface defines a surface where every point is a weighted sum of  $(m+1) \times (n+1)$  control points.

$$p(u, v) = \sum_{i=0}^{n} \sum_{j=0}^{m} B_i^n(u) B_j^m(v)$$


$$B_i^n(u) = \binom{n}{i} u^i (1 - u)^{n-i}$$

$$\binom{n}{i} = \frac{n!}{i!(n-i)!}$$



### Bezier Surface to Mesh

#### Fewer samples



- A Bezier surface could be used directly for rendering, but it is usually converted to a mesh (tessellation), which is easier to render.
  - Sample the Bezier surface by calculating a set of points, which become mesh vertices.
  - Description Connect these vertices generates a mesh.
  - Sampling could be uniform, or could be non-uniform (e.g., more sample when curvature is higher).

https://en.wikipedia.org/wiki/B%C3%A9zier\_curve

### Point Cloud/Point Set



### Laser Scanner



Laser scanner.



From Mike Jarvis, Prof. @ History Dept. Scanning Elmina Castle, a UNESCO World Heritage Site at Ghana.

### LiDAR





Velodyne LiDAR (Light Detection and Ranging)

Uber's self-driving car equipped with LiDARs




### LiDAR











### Point Set Triangulation

Point set could be used directly for rendering (point-based graphics), but it is usually converted to a mesh, which is easier to render.



Delaunay triangulation: no point is inside the circumcircle of any triangle.



### Additional Readings

- ▶ <u>Tessellation of 4x4 Bezier Patches for the Intel Pentium III Processor</u>
- ▶ <u>Bézier Curves and Surfaces: the Utah Teapot</u>. A series of articles from scratchapixel on Bezier curves and surfaces.