

Iterated Limiting Recursion and the Program Minimization Problem

L. K. SCHUBERT

University of Alberta, Edmonton, Alberta, Canada

ABSTRACT. The general problem of finding minimal programs realizing given "program descriptions" is considered, where program descriptions may be of finite or infinite length and may specify arbitrary program properties. The problem of finding minimal programs consistent with finite or infinite input-output lists is a special case (for infinite input-output lists, this is a variant of E. M. Gold's function identification problem). Although most program minimization problems are not recursively solvable, they are found to be no more difficult than the problem of deciding whether any given program realizes any given description, or the problem of enumerating programs in order of nondecreasing length (whichever is harder). This result is formulated in terms of k -limiting recursive predicates and functionals, defined by repeated application of Gold's limit operator. A simple consequence is that the program minimization problem is limiting recursively solvable for finite input-output lists and 2-limiting recursively solvable for infinite input-output lists, with weak assumptions about the measure of program size. Gold regarded limiting function identification (more generally, "black box" identification) as a model of inductive thought. Intuitively, iterated limiting identification might be regarded as higher-order inductive inference performed collectively by an ever-growing community of lower order inductive inference machines.

KEY WORDS AND PHRASES: minimal programs, limiting recursion, function identification, inductive inference, degree of unsolvability, Kleene hierarchy, program properties, program length measures

CR CATEGORIES: 3.61, 5.27

1. Introduction

A question considered by Gold [1] was for what classes of computable functions there exist machines which succeed in "identifying in the limit" any member of the class. Identifying a computable function in the limit consists of generating a sequence of "guesses" (integers) convergent to an index for the function, successive guesses being based on successively larger portions of an information sequence which lists all elements of the function. An example of a practical problem to which these concepts are relevant is the learning problem in pattern recognition. Typically an adaptive pattern recognition system is caused to "learn" a mapping from patterns to responses by presenting to it a sequence of labeled patterns, i.e. patterns with their appropriate responses. All of the machine's responses will be correct once it has identified the pattern-response mapping, in the sense that it has found an algorithm (equivalently, an index) for it. Two of Gold's main results were that any r.e. class of total recursive functions is identifiable in the limit, and that the class of total recursive functions is not identifiable in the limit (hence also the class of partial recursive functions is not identifiable in the limit).

Copyright © 1974, Association for Computing Machinery, Inc. General permission to republish, but not for profit, all or part of this material is granted provided that ACM's copyright notice is given and that reference is made to the publication, to its date of issue, and to the fact that reprinting privileges were granted by permission of the Association for Computing Machinery.

This work was conducted under a National Research Council Postdoctorate Fellowship.

Author's address: Department of Computing Science, University of Alberta, Edmonton 7, Alberta, Canada.



Here a modified version of Gold's problem is considered. The first modification is the replacement of information sequences by (finite or infinite) "program descriptions" which may specify arbitrary program properties. Descriptions which list input-output pairs are then regarded as a special case. The second modification is that iterated limit procedures (k -limiting recursive functionals) are admitted for program finding, since finding suitable programs in the noniterated limit is impossible for many classes of program descriptions. For this purpose k -limiting recursiveness is defined by straightforward generalization of Gold's concept of limiting recursiveness. The third modification is the added requirement that programs found in the (iterated) limit be minimal according to some prescribed measure of program size. Accordingly problems of this modified type are called program minimization problems.

There are various reasons for an interest in finding minimal-length programs. In work on grammatical inference closely related to Gold's identification problem, Feldman [2] considers inference schemes which try to find "good" grammars consistent with available information about a language. One measure of goodness is the intrinsic complexity, or size, of a grammar. In terms of the function identification problem, this corresponds to finding programs which are small according to some measure of program size. Indeed, the use of small (though not necessarily minimal) programs for inductive inference is a recurring theme in the literature (see, for example, [3-5]); allusion is usually made to the scientific maxim known as "Occam's Razor," according to which "it is vain to do with more what can be done with fewer" in accounting for known phenomena. The special importance of minimal programs is also suggested by the work of Kolmogorov [6], Martin-Löf [7], and others, showing that the number of symbols in the shortest program for generating a finite sequence can be taken as a measure of the information content of the sequence, and this measure provides a logical basis for information theory and probability theory.

In the following the unsolvability of most nontrivial program minimization problems is first noted. After establishment of some basic properties of k -limiting recursive predicates and functionals, it is shown that any program minimization problem is k -limiting recursively solvable if the problem of determining whether any given program satisfies any given description is k -limiting recursively solvable and programs are k -limiting r.e. in order of nondecreasing size. Simple consequences are that the problem of finding minimal programs for finite functions is limiting recursively solvable, and that the problem of finding minimal programs for arbitrary computable functions (given an explicit listing) is 2-limiting recursively solvable, with weak assumptions about the measure of program size. Lower bounds on the difficulty of these problems are already known from the work of Pager [8] and Gold [1].

Finally, the point is emphasized in the concluding remarks that limiting recursively solvable induction problems, though strictly "unsolvable" in general, are nonetheless within the reach of mechanical procedures in the important sense described by Gold, and that even problems unsolvable in the limit may be regarded as solvable in a weakened sense by an expanding community of mechanisms performing limit computations.

2. Program Minimization Problems

To fix ideas, any *programmable machine* M may be thought of as a 2-tape Turing machine, with one tape regarded as input-output (I/O) tape and the other as program tape. One or both tapes also serve as working tape. A computation begins with the finite-state control of the machine in a unique start state and with a program on the program tape and an input on the I/O tape. If and when the machine halts, the I/O tape expression gives the output. It is assumed that there is an effective 1-1 coding from tape expressions (same syntax for both tapes) onto the integers N . The program (or I/O tape expression) corresponding to code number (index) x will be written as \bar{x} . If M eventually halts with output \bar{z} when supplied with program \bar{x} and input \bar{y} , one may write $\phi_x^M(y) = z$. If M

does not halt, $\phi_x^M(y)$ is undefined. Thus M computes a partial function ϕ_x^M with program \bar{x} . However, it will be convenient to think of \bar{x} not merely as a program for ϕ_x^M , but as a program for any subset of ϕ_x^M . In other words, \bar{x} is a program for a function ϕ provided only that $\phi_x^M(y) = \phi(y)$ for all y in the domain of ϕ ; $\phi_x^M(y)$ need not be undefined for y outside that domain. If such an \bar{x} exists for a given ϕ , ϕ will be said to be *programmable* (on M). A machine M such that the sequence $\phi_0^M, \phi_1^M, \phi_2^M, \dots$ contains every partial recursive function is *universal*.

A *program length measure* assigns a nonnegative integral length to each program such that only a finite number of programs are of any particular length. The length of a program \bar{x} will be denoted by $|x|$. A length measure need not be recursive, though this is a frequent assumption; furthermore, programs are often assumed to be effectively enumerable in order of nondecreasing length. For example, the number of elementary symbols in a program provides such a length measure.

In the following, obviously machine and length-measure dependent concepts will sometimes be used without explicit reference to a particular machine or length measure. This should be kept in mind for a correct interpretation of the results.

A minimal program for a function ϕ is one whose length does not exceed the length of any other program for ϕ . The problem of finding a minimal program (or all minimal programs) for a function ϕ , given a (possible infinite) list of the argument-value pairs of ϕ , is an example of a *program minimization problem*. More generally, a program minimization problem is the problem of finding a minimal program (or all minimal programs) meeting the conditions listed in any "program description" belonging to some class of such descriptions. Program descriptions are loosely defined as follows. Suppose that a (possibly infinitary) logical system is given along with an interpretation based on a fixed M such that every wff in the system expresses some program property (i.e. every wff is a unary predicate over programs). Then the wff's comprising the system will be called *program descriptions*. Typically a program description might specify relationships between inputs and outputs (e.g. particular input-output pairs), structural properties (e.g. the number of occurrences of a particular symbol in the program), operational properties (e.g. computational complexity), or combinations of such properties. If δ is a program description, a program \bar{x} will be said to *realize* δ if \bar{x} has the property expressed by δ ; more briefly, $\delta(\bar{x})$ will be written for " \bar{x} realizes δ ." If an \bar{x} exists such that $\delta(\bar{x})$, then δ will be said to be *realizable*. For some descriptions (such as listings of input-output pairs) the truth value of the assertion $\delta(\bar{x})$ depends only on the function computed by M with program \bar{x} , i.e. $[\phi_x^M = \phi_y^M] \Rightarrow [\delta(\bar{x}) \Leftrightarrow \delta(\bar{y})]$. Such descriptions will be termed I/O descriptions. As examples of I/O descriptions which do *not* merely list functions, consider the following expressions (in a quasilogical notation with the obvious interpretation):

- (i) $[\phi_x^M(3) = 9 \vee \phi_x^M(3) = 11] \& \phi_x^M(5)$ divergent,
- (ii) $(\forall y)[\phi_x^M(y)$ convergent & even],
- (iii) $(\forall y)[\phi_x^M(y) = \phi_{75}^M(y)] \vee (\forall y)[\phi_x^M(y + 5) = \phi_x^M(y) + 6]$.

Gold's identification problem can evidently be reformulated in terms of infinite descriptions (i.e. wff's belonging to an infinitary logical system) such as

- (iv) $\phi_x^M(0) = 0 \& \phi_x^M(1) = 1 \& \phi_x^M(2) = 4 \& \phi_x^M(3) = 9 \& \dots$, etc.

It is assumed that descriptions can be coded numerically. If only finite descriptions are involved, an effective coding of descriptions into integers is appropriate. If infinite descriptions are involved, these can be coded as total number-theoretic functions on N by means of a 1-1 mapping from elementary symbols into integers.¹ For example, consider illustration (iv) above; if the numbers from 1 to 5 are used to encode the symbols

¹ A code into total functions would also be used for a mixture of finite and infinite descriptions; one digit, say 0, would be reserved as terminator and all function values corresponding to points beyond the end of a finite description would be set to 0.

ϕ_x^M , $(,)$, $=$, and $\&$, respectively, and numerals within the description are represented by adding 6, the code sequence 1, 2, 6, 3, 4, 6, 5, 1, 2, 7, 3, 4, 7, 5, \dots is obtained; expressed as a total function this is $\{\langle 0, 1 \rangle, \langle 1, 2 \rangle, \langle 2, 6 \rangle, \langle 3, 3 \rangle, \langle 4, 4 \rangle, \langle 5, 6 \rangle, \dots\}$. Thus when functions of encoded descriptions are considered later on, these become *functionals* in the case of infinite descriptions.

The coded version of a description δ , whether it is finite or infinite, will be written as δ . Since no confusion can result, coded representations of descriptions will also simply be called descriptions. A set of descriptions will be called *infinitely diverse* if every set of programs containing at least one that realizes any given one of the descriptions is infinite. Otherwise the descriptions are *finitely diverse*, i.e. some finite set of programs suffices for their realization.

Theorem 1 is concerned with I/O descriptions only, while Theorems 3 and 4 will apply to arbitrary program descriptions.

THEOREM 1. *Let M be a universal programmable machine and let a recursive length measure be given. Then the program minimization problem is not recursively solvable for any effectively enumerable, infinitely diverse set of I/O descriptions.*

PROOF. Pagar [8] previously noted this fact for the case when I/O descriptions specify finite functions, and remarked that the proof involves the Recursion Theorem. The theorem also follows directly from a theorem of Blum [9]. The denial of the theorem allows an infinite set of minimal programs to be enumerated, by enumeration of the I/O descriptions and computation of the corresponding minimal programs. If $h(x, y)$ is a function which simulates the first minimal program enumerated of size greater than $|x|$, then clearly $h(x, y)$ is partial recursive, and hence by the S - m - n Theorem and the Recursion Theorem, for some x_0 , $h(x_0, y) = \phi_{x_0}^M(y)$ for all y . Thus x_0 is shorter than one of the supposed minimal programs in the enumeration.

To demonstrate the unsolvability of a program minimization problem (for a universal machine), it is therefore sufficient to show that the descriptions concerned include an effectively enumerable, infinitely diverse set of I/O descriptions. This implies, for example, that the program minimization problem for the singleton functions, for the finite decision functions, and even for the decision functions of cardinality 2 is unsolvable,² whenever the length measure is recursive.

Pagar [10] has shown that the last-mentioned problem is unsolvable even when the length measure is not recursive. Further, he established the surprising fact that the minimization problem is unsolvable for a certain *finitely diverse* set of decision functions, regardless of the length measure employed [8].

In view of Pagar's results it may be asked whether the requirement that the length measure be recursive is superfluous in Theorem 1. The answer is no (although the requirement can be weakened somewhat). To prove this, it is only necessary to specify some sequence of finite decision functions such that any program is a program for at most one of these functions, plus an arbitrary procedure for obtaining a particular program for each function in the sequence; then the length measure can readily be defined to guarantee the minimality of these particular programs.

It is interesting to note that Theorem 1 still holds for certain non-I/O descriptions. For example, suppose the minimal programs are required to operate within a certain bound on the computational complexity (e.g. time or tape complexity), apart from an arbitrary additive constant. Then it is clear that the proof of Theorem 1 is applicable without change.

² For the finite decision functions, note that the functions computed with any finite set of programs can be diagonalized to yield a finite decision function which requires a program not in the given set. To prove infinite diversity for the 2-element decision functions, it is sufficient to show that no set of n programs can include a program for each 2-element decision function whose arguments are in a fixed set of 2^{n+1} integers; but for this many arguments at least 2 of the programs must give identical results (if any), so that two unsymmetric decision functions are missed.

These unsolvability results do not mean that all interesting program minimization problems are entirely beyond the reach of mechanical procedures, as Theorem 3 will show.

The following definitions generalize the concept of limiting recursion introduced by Gold [1].

Definitions. Let Δ be a subset of $\Phi_1 \times \cdots \times \Phi_r \times N^s$ where the Φ_i are sets of unary total functions and $r, s \geq 0$. A functional³ F is *k-limiting recursive* on Δ if there exists a functional G recursive on $\Delta \times N^k$ such that

$$(\forall \delta \in \Delta)(\exists m_1)(\forall n_1 > m_1) \cdots (\exists m_k)(\forall n_k > m_k)[F(\delta) = G(\delta, n_1, \dots, n_k)].$$

Equivalently one may write $(\forall \delta \in \Delta)[\lim_{n_1} \cdots \lim_{n_k} G(\delta, n_1, \dots, n_k) = F(\delta)]$.⁴ For $k = 1$, these statements say that for all arguments δ , $G(\delta, n)$ is the same as $F(\delta)$ whenever n is sufficiently large, or equivalently, that the limit of $G(\delta, n)$ with respect to n is $F(\delta)$ (the limit is attained in finitely many steps); for $k = 2$, they say that for all arguments δ and all sufficiently large n_1 , $G(\delta, n_1, n_2)$ is the same as $F(\delta)$ whenever n_2 is sufficiently large, or equivalently, that in the limit of large n_1 the limit of $G(\delta, n_1, n_2)$ with respect to n_2 is $F(\delta)$; etc. It can be shown (with the aid of the Kleene T -predicate and the Recursion Theorem) that for all k there are $(k + 1)$ -limiting recursive functionals that are *not* k -limiting recursive. Similarly a predicate P is *k-limiting decidable* on Δ if there is a predicate Q decidable on $\Delta \times N^k$ such that $(\forall \delta \in \Delta)(\exists m_1)(\forall n_1 > m_1) \cdots (\exists m_k)(\forall n_k > m_k)[P(\delta) \equiv Q(\delta, n_1, \dots, n_k)]$. Descriptions comprising a set Δ will be called *uniformly k-limiting decidable* (with a particular M understood) if there is a predicate P k -limiting decidable on $\Delta \times N$ such that for all $\delta \in \Delta$, $P(\delta, x)$ holds iff $\delta(\bar{x})$. A set of integers is *k-limiting r.e.* if it is empty or the range of a function k -limiting recursive on N .⁵ 0-limiting recursive is the same as recursive, and 1-limiting recursive is abbreviated as limiting recursive.

Gold (also Putnam [11]) has shown that limiting decidable is equivalent to membership in the intersection of classes Σ_2 and Π_2 of the Kleene arithmetical hierarchy. It can be shown that if P is k -limiting r.e., then it is in Σ_{2k} and if P is k -limiting decidable, it is in $\Sigma_{2k} \cap \Pi_{2k}$, for all k . I conjecture the converse statements to be false for $k > 1$; the proof (or disproof) of this conjecture is an open problem. The following is easily verified.

LEMMA 1. *If P and Q are predicates of at least one number variable (and possibly additional number and function variables), then $(\exists m)(\forall n > m)P(n, \dots) \& (\exists m)(\forall n > m)Q(n, \dots) \equiv (\exists m)(\forall n > m)[P(n, \dots) \& Q(n, \dots)]$.*

COROLLARY 1.1. *If P and Q are predicates of at least k number variables (and possibly additional number and function variables), then*

$$\begin{aligned} & (\exists m_1)(\forall n_1 > m_1) \cdots (\exists m_k)(\forall n_k > m_k)P(n_1, \dots, n_k, \dots) \\ & \quad \& (\exists m_1)(\forall n_1 > m_1) \cdots (\exists m_k)(\forall n_k > m_k)Q(n_1, \dots, n_k, \dots) \\ \equiv & (\exists m_1)(\forall n_1 > m_1) \cdots (\exists m_k)(\forall n_k > m_k)[P(n_1, \dots, n_k, \dots) \& Q(n_1, \dots, n_k, \dots)]. \end{aligned}$$

LEMMA 2. *Composition of k -limiting recursive functionals yields a k -limiting recursive functional.*

PROOF. Consider the special case $F' = \lambda\phi\psi xy[F(\phi, x, H(\psi, y))]$, where F and H are functionals k -limiting recursive on $\Phi \times N^2$ and $\Psi \times N$ respectively, and Φ, Ψ are sets of total functions. The proof is easily extended to the case where F is r -ary and s of its arguments are values of k -limiting recursive functionals H_1, H_2, \dots, H_s . Since F and H are k -limiting recursive, there exist functionals G and K recursive on $\Phi \times N^{k+2}$ and $\Psi \times N^{k+1}$ respectively such that

$$\begin{aligned} & (\forall \phi \in \Phi)(\forall x)(\forall z)(\exists m_1)(\forall n_1 > m_1) \cdots (\exists m_k)(\forall n_k > m_k)[F(\phi, x, z) \\ & \quad = G(\phi, x, z, n_1, \dots, n_k)], \quad (1) \end{aligned}$$

³ Functions are regarded as a special case of functionals.

⁴ The equivalence follows from the fact that $F(\delta)$ is independent of n_1, \dots, n_k , so that the iterated limit of G must exist.

⁵ This differs from Gold's definition, which expresses limiting recursive enumerability in terms of limiting semidecidability. However, the definitions can be shown to be equivalent (for $k = 1$).

and

$$(\forall \psi \in \Psi)(\forall y)(\exists m_1)(\forall n_1 > m_1) \cdots (\exists m_k)(\forall n_k > m_k)[H(\psi, y) = K(\psi, y, n_1, \dots, n_k)]. \quad (2)$$

Since $H(\psi, y)$ is defined for all $\psi \in \Psi$ and all y , a consequence of (1) is

$$(\forall \phi \in \Phi)(\forall \psi \in \Psi)(\forall x)(\forall y)(\exists m_1)(\forall n_1 > m_1) \cdots (\exists m_k)(\forall n_k > m_k) [F(\phi, x, H(\psi, y)) = G(\phi, x, H(\psi, y), n_1, \dots, n_k)]. \quad (3)$$

By Corollary 1.1, (2) and (3) then give

$$(\forall \phi \in \Phi)(\forall \psi \in \Psi)(\forall x)(\forall y)(\exists m_1)(\forall n_1 > m_1) \cdots (\exists m_k)(\forall n_k > m_k) [F(\phi, x, H(\psi, y)) = G(\phi, x, K(\psi, y, n_1, \dots, n_k), n_1, \dots, n_k)],$$

so that F' is k -limiting recursive on $\Phi \times \Psi \times N^2$. Note that it has also been shown that a recursive functional whose iterated limit is the desired composed functional can be obtained simply by composing the recursive functionals whose iterated limits are the given functionals.

COROLLARY 2.1. *A predicate whose characteristic function(al) is expressible as a composition of k -limiting recursive function(al)s is k -limiting decidable.*

For example, let the unary predicates P and Q have k -limiting recursive characteristic functions C_P and C_Q , and let $f(x, y) = xy$ for all x and y ; then R defined as $R(x) \equiv P(x) \& Q(x)$ is k -limiting decidable, since $C_R(x) = f(C_P(x), C_Q(x))$ for all x and f is recursive and hence k -limiting recursive for all k .

LEMMA 3. *Application of the minimization operator to a k -limiting decidable predicate yields a k -limiting recursive functional, provided the requisite minimal value always exists.*

For example, if P is k -limiting decidable on $\Phi \times N^2$, where Φ is a class of total functions, then $\lambda \phi x [\mu y P(\phi, x, y)]$ is k -limiting recursive on $\Phi \times N$, provided $(\forall \phi \in \Phi)(\forall x)(\exists y)P(\phi, x, y)$. The notation " $\mu y \dots$ " stands for "the least y such that \dots ".

PROOF. Consider the ternary predicate P above (extension to the general case is straightforward). Let $y_{\phi x}$ be the Skolem functional in the existence criterion above, i.e. $(\forall \phi \in \Phi)(\forall x)P(\phi, x, y_{\phi x})$. Since P is k -limiting decidable, $(\forall \phi \in \Phi)(\forall x)(\forall y)(\exists m_1)(\forall n_1 > m_1) \cdots (\exists m_k)(\forall n_k > m_k)[P(\phi, x, y) \equiv Q(\phi, x, y, n_1, \dots, n_k)]$ where Q is decidable on $\Phi \times N^{k+2}$. Restrict y to $y \leq y_{\phi x}$, so that the $(\forall y)$ quantifier becomes $(\forall y \leq y_{\phi x})$. This bounded quantifier may be passed through the others:

$$(\forall \phi \in \Phi)(\forall x)(\exists m_1)(\forall n_1 > m_1) \cdots (\exists m_k)(\forall n_k > m_k)(\forall y \leq y_{\phi x}) [P(\phi, x, y) \equiv Q(\phi, x, y, n_1, \dots, n_k)].$$

Hence

$$(\forall \phi \in \Phi)(\forall x)(\exists m_1)(\forall n_1 > m_1) \cdots (\exists m_k)(\forall n_k > m_k) [(\mu y \leq y_{\phi x})P(\phi, x, y) = (\mu y \leq y_{\phi x})Q(\phi, x, y, n_1, \dots, n_k)].$$

Now since $P(\phi, x, y_{\phi x})$ holds, $(\mu y \leq y_{\phi x})P(\phi, x, y) = \mu y P(\phi, x, y)$. But $[\mu y P(\phi, x, y) = (\mu y \leq y_{\phi x})Q(\phi, x, y, n_1, \dots, n_k)]$ is equivalent to $[\mu y P(\phi, x, y) = \mu y Q(\phi, x, y, n_1, \dots, n_k)]$ from the definition of $y_{\phi x}$, and this is in turn equivalent to $[\mu y P(\phi, x, y) = \mu y [Q(\phi, x, y, n_1, \dots, n_k) \vee y = n_1]]$ provided $n_1 > y_{\phi x}$. Since the right side of the bracketed equality expresses a functional recursive on $\phi \times N^{k+1}$ and since m_1 can be chosen greater than $y_{\phi x}$, $\mu y P(\phi, x, y)$ is k -limiting recursive on $\Phi \times N$.

THEOREM 2. *For any k -limiting recursive length measure, programs are $(k + 1)$ -limiting r.e. in order of nondecreasing length.*

PROOF. There exists a recursive function f such that

$$(\forall x)(\exists m_1)(\forall n_1 > m_1) \cdots (\exists m_k)(\forall n_k > m_k)[f(x, n_1, \dots, n_k) = |x|]. \quad (4)$$

Let $g(i) = (\mu x \in S_i)(\forall y \in S_i)[|x| \leq |y|]$ for all i , where $S_0 = N$, $S_{i+1} = S_i - \{g(i)\}$. Thus g enumerates programs (actually, their indices) in order of nondecreasing

length. Analogously let $h(i, n, n_1, \dots, n_k) = (\mu x \in S_{in})(\forall y \in S_{in})[f(x, n_1, \dots, n_k) \leq f(y, n_1, \dots, n_k)]$ for all i, n, n_1, \dots, n_k , where $S_{0n} = \{0, \dots, n\}$, $S_{i+1,n} = (S_{in} - \{h(i, n, n_1, \dots, n_k)\}) \cup \{n\}$ for all i, n . As S_{in} is finite for all i, n and f is recursive, h is also recursive.

For $x \leq n$ the first quantifier in (4) is bounded and can be passed through the others:

$$(\exists m_1)(\forall n_1 > m_1) \cdots (\exists m_k)(\forall n_k > m_k)(\forall x \leq n)[f(x, n_1, \dots, n_k) = |x|]. \quad (5)$$

From the definition of h

$$(\forall i)(\forall n)(\exists m_1)(\forall n_1 > m_1) \cdots (\exists m_k)(\forall n_k > m_k)[h(i, n, n_1, \dots, n_k) = (\mu x \in S_{in})(\forall y \in S_{in})[f(x, n_1, \dots, n_k) \leq f(y, n_1, \dots, n_k)]]. \quad (6)$$

By Corollary 1.1, (5) and (6) give

$$(\forall i)(\forall n)(\exists m_1)(\forall n_1 > m_1) \cdots (\exists m_k)(\forall n_k > m_k)[h(i, n, n_1, \dots, n_k) = (\mu x \in S_{in})(\forall y \in S_{in})[f(x, n_1, \dots, n_k) \leq f(y, n_1, \dots, n_k)] \& (\forall x \leq n)[f(x, n_1, \dots, n_k) = |x|] \& (\forall y \leq n)[f(y, n_1, \dots, n_k) = |y|]].$$

Since $x, y \leq n$ in the definition of h ,

$$(\forall i)(\forall n)(\exists m_1)(\forall n_1 > m_1) \cdots (\exists m_k)(\forall n_k > m_k)[h(i, n, n_1, \dots, n_k) = (\mu x \in S_{in})[|x| \leq |y|]]. \quad (7)$$

For any given i , let $m = \max\{g(j) \mid j \leq i\}$. Then for all $n > m$, all $j \leq i$, and all choices of n_1, \dots, n_k which guarantee the equality in (7), it is easily shown by induction on j that $S_{jn} = S_j - \{x \mid x > n\}$ and $h(j, n, n_1, \dots, n_k) = g(j)$. Hence

$$(\forall i)(\exists m)(\forall n > m)(\exists m_1)(\forall n_1 > m_1) \cdots (\exists m_k)(\forall n_k > m_k)[h(i, n, n_1, \dots, n_k) = g(i)],$$

so that g is $(k+1)$ -limiting recursive.

Some examples of sets of program descriptions may help the reader interpret the theorems that follow. An example of a set of uniformly (0-limiting) decidable descriptions is $\Delta = \{\text{the program converges in at most } i^2 \text{ steps on the first } i \text{ inputs; the output of the program on each of the first } i \text{ inputs is } i \mid i \in N\}$. An example of a set of uniformly limiting decidable descriptions is $\Delta = \{\text{for any input } n, \text{ the program converges in at most } (i+n)^{i+n} \text{ steps with output } i+n \mid i \in N\}$; a set of infinitely long descriptions equivalent to the last (and still limiting decidable) is $\Delta = \{\text{each of the following triples gives an input, corresponding output, and corresponding maximum number of steps for the program to converge: } \langle 0, i, i^i \rangle, \langle 1, i+1, (i+1)^{i+1} \rangle, \langle 2, i+2, (i+2)^{i+2} \rangle, \dots, \mid i \in N\}$.

Roughly speaking, Theorem 3 states that finding minimal programs is no more difficult than enumerating programs in order of nondecreasing length or deciding whether a given program realizes a given description (whichever is harder), where the "difficulty" of a k -limiting recursive functional is k .

THEOREM 3. *Given: a programmable machine M , a length measure such that programs are k -limiting r.e. in order of nondecreasing length, and a set Δ of realizable, uniformly k -limiting decidable program descriptions. Then the program minimization problem for Δ is k -limiting recursively solvable.*

PROOF. Since programs are k -limiting r.e. in order of nondecreasing length, there is a k -limiting recursive function f which maps N onto N such that $j > i \Rightarrow |f(j)| \geq |f(i)|$. Also, since program descriptions are uniformly k -limiting decidable, there is a k -limiting decidable predicate P such that for all $\delta \in \Delta$ and $x \in N$, $P(\delta, x) \Leftrightarrow \delta(\bar{x})$.

Let $i_\delta = \mu i P(\delta, f(i))$; thus $\bar{f}(i_\delta)$ is the first minimal program realizing δ in the sequence $\bar{f}(0), \bar{f}(1), \dots$. By the lemmas, i_δ is k -limiting recursive on Δ .

THEOREM 4. *Given: a k -limiting recursive length measure such that programs are k -limiting r.e. in order of nondecreasing length and a set Δ of realizable, uniformly k -limiting*

decidable program descriptions. Then the problem of finding all minimal programs realizing any $\delta \in \Delta$ is k -limiting recursively solvable.

PROOF. Define i_δ as in the proof of Theorem 3 and let $i'_\delta = \mu i [|f(i)| > |f(i_\delta)|]$. The predicate expressed by the bracketed inequality, with i and δ regarded as variables, is k -limiting decidable by Lemma 2, as f , i_δ , $| \cdot |$, and the characteristic function of $\{ \langle x, y \rangle \mid x > y \}$ are all k -limiting recursive. Hence by Lemma 3, i'_δ is k -limiting recursive on Δ .

Now if the set of indices of the minimal programs realizing δ is expressed by its canonical index $u_\delta = \sum_{i=0}^{i'_\delta} 2^{f(i)} C_P(\delta, f(i))$, where C_P is the characteristic function of P , with P defined as in Theorem 3, then application of Lemma 2 shows u_δ to be k -limiting recursive on Δ .

Note that because of the assumption in Theorem 4 that the length measure is k -limiting recursive, Theorem 3 cannot be regarded as a consequence of Theorem 4. Note also that any $(k - 1)$ -limiting recursive length measure satisfies the conditions of Theorem 4 (by Theorem 2).

Theorems 3 and 4 are the main results of this paper. The remaining theorems illustrate their application.

THEOREM 5. For any recursive length measure, the problem of finding all minimal programs for finite programmable functions is limiting recursively solvable (each finite function is assumed to be specified by a program description which lists the argument-value pairs of the function in any order).

PROOF. By Theorem 2, programs are limiting r.e. in order of nondecreasing length. Let the finite function encoded by any particular $\delta \in \Delta$ be $\{ \langle y_i^\delta, z_i^\delta \rangle \mid i \leq n_\delta \}$. Let $Q = \{ \langle \delta, x, n \rangle \mid \text{for all } i \leq n, M \text{ with program } \bar{x} \text{ and input } \bar{y}_i^\delta \text{ halts within } n \text{ steps with output } \bar{z}_i^\delta \}$. Clearly Q is decidable and $(\forall \delta \in \Delta)(\forall x)(\exists m)(\forall n > m)[Q(\delta, x, n) \equiv P(\delta, x)]$, where $P(\delta, x) \Leftrightarrow \delta(\bar{x})$. Hence the problem of finding all minimal programs for any finite function is limiting recursively solvable. (Use of Theorem 2 could easily have been avoided.)

THEOREM 6. Given a recursive length measure and a machine M which computes total functions only, the problem of finding minimal programs for functions programmable on M is limiting recursively solvable (each programmable function is assumed to be specified by a program description which lists the argument-value pairs of the function in any order).

PROOF. For all i , let $\langle y_i^\delta, z_i^\delta \rangle$ be the i th argument-value pair specified by any description δ , and let $Q = \{ \langle \delta, x, n \rangle \mid \text{for all } i \leq n, M \text{ with program } \bar{x} \text{ and input } \bar{y}_i^\delta \text{ computes output } \bar{z}_i^\delta \}$. Q is decidable since M always halts; if there is an m such that M fails to output \bar{z}_m^δ with program \bar{x} and input \bar{y}_m^δ , then $Q(\delta, x, n)$ will be false for all $n > m$; if there is no such m (so that \bar{x} realizes δ), then $Q(\delta, x, n)$ is true for all n . Evidently the descriptions are uniformly limiting decidable and the theorem follows.

Gold had already shown that the problem of finding any programs (not necessarily minimal) for members of an r.e. class of total functions is limiting recursively solvable, and Feldman [2] remarked that this can be extended in an obvious way to finding minimal programs⁶ when programs are r.e. in order of nondecreasing length. Theorem 6 strengthens this result slightly, as there are recursive length measures for which programs are not r.e. in order of nondecreasing length (e.g. define $| \cdot |$ so that the sequence $|0|, |1|, |2|, \dots$ enumerates an r.e., nonrecursive set without repetition).

THEOREM 7. For any M and any limiting recursive length measure, the problem of finding minimal programs for functions programmable on M is 2-limiting recursively solvable (as in Theorem 6, the problem is interpreted in terms of program descriptions, where any description lists the argument-value pairs of a programmable function in any order).

PROOF. Let $Q = \{ \langle \delta, x, n_1, n_2 \rangle \mid \text{for all } i \leq n_1, M \text{ with program } \bar{x} \text{ and input } \bar{y}_i^\delta \text{ halts within } n_2 \text{ steps with output } \bar{z}_i^\delta \}$, with y_i^δ, z_i^δ defined as in Theorem 6. For fixed δ, x, n_1 ,

⁶ Actually, Feldman was concerned with "occams enumerations" of formal grammars, but the problem of finding minimal grammars for languages is essentially the same as that of finding minimal programs for decision functions.

$Q(\delta, x, n_1, n_2)$ holds in the limit of large n_2 iff \bar{x} is a program for $\{\langle y_i^\delta, z_i^\delta \rangle \mid i \leq n_1\}$. If \bar{x} is a program for $\{\langle y_i^\delta, z_i^\delta \rangle \mid i \in N\}$, then $(\forall n_1) \lim_{n_2} Q(\delta, x, n_1, n_2)$; if not, there is a pair $\langle y_m^\delta, z_m^\delta \rangle$, contained in all sets $\{\langle y_i^\delta, z_i^\delta \rangle \mid i \leq n_1\}$ for which $n_1 > m$, such that M with program \bar{x} fails to compute output \bar{z}_m^δ for input \bar{y}_m^δ ; hence $(\forall n_1 > m) \neg \lim_{n_2} Q(\delta, x, n_1, n_2)$. It follows that the descriptions are uniformly 2-limiting decidable. Since programs are 2-limiting r.e. in order of nondecreasing length by Theorem 2, the program minimization problem is 2-limiting recursively solvable.

Note that it is known from the work of Gold that the problem is not in general limiting recursively solvable.

The theorem is readily generalized to descriptions which prescribe divergent computations for some inputs. The minimization problem remains 2-limiting recursively solvable.

3. Remarks on Induction and Iterated Limiting Recursion

Deduction is concerned with the derivation of particular consequences from general premises, while induction proceeds in the opposite direction. The problem of finding an algorithm (minimal or otherwise) for a function, after inspection of some but not all values of the function, is clearly of the inductive type: the complete algorithm proposed on the basis of incomplete information expresses a generalization about the function sampled. Nontrivial inductive problems are inherently "unsolvable" in the sense that no terminating procedure exists for generating "correct" generalizations; any unverified consequence of a proposed generalization may turn out to be in error. This motivated Gold's definition of limiting recursive predicates and functionals, which are more powerful than their nonlimiting counterparts. He noted that a "thinker" employing a procedure for function (or "black-box") identification in the limit and using the current guess of a function's identity as a basis for goal-directed activity would be acting on correct information eventually. *In this sense, therefore, some unsolvable problems are within the reach of mechanical procedures.* The most general function identification problem, however, is 2-limiting recursive. Can any mechanical system be conceived which in some sense "solves" a 2-limiting recursive problem? Not if attention is restricted to a single "thinker" generating a single sequence of guesses; however, suppose that instead of a single thinker, each of an ever-growing number of such thinkers T_0, T_1, \dots with universal computational power observes the nonterminating sequence $\langle y_0, z_0 \rangle, \langle y_1, z_1 \rangle, \dots$ which enumerates some partial recursive function ϕ . At any time the i th thinker T_i regards as his best guess the shortest program (if any) he has been able to find which, in the time available, has given correct outputs for inputs y_0, y_1, \dots, y_i and either no output or a correct output for any other argument tested. It is clear that each thinker will eventually be guessing a program for a subset of ϕ ; furthermore, all but a finite number of the thinkers will be guessing programs for ϕ eventually. In this iterated limiting sense the expanding community successfully identifies ϕ . Of course there is no strategy effective in the limit for deciding in general which thinkers are guessing programs for ϕ at any time. To interpret third-order limit processes, one might envisage a growing number of expanding communities of the above type, each committed to a distinct value of a certain parameter. At most finitely many of the unbounded communities would in general be "unsuccessful." Similarly still higher-order processes could be interpreted.

ACKNOWLEDGMENTS. I am indebted to C. G. Morgan for several stimulating and helpful discussions and to J. R. Sampson for his many useful comments on the manuscript. I. N. Chen's help on some aspects of the paper is also gratefully acknowledged.

REFERENCES

1. GOLD, E. M. Limiting recursion. *J. Symb. Logic* 10 (1965), 28-48.
2. FELDMAN, J. Some decidability results on grammatical inference and complexity. Stanford Artif. Intel. Project Memo AI-93, 1969; also *Inform. and Contr.* 20 (1972), 244-262.

3. SOLOMONOFF, R. A formal theory of inductive inference. *Inform. and Contr.* 7 (1964), 1-22, 224-254.
4. CHAITIN, G. On the difficulty of computations. *IEEE Trans. Inf. Theory*. IT-16 (1970), 5-9.
5. WILLIS, D. G. Computational complexity and probability constructions. *J. ACM* 17, 2 (April 1970), 241-259.
6. KOLMOGOROV, A. N. Three approaches to the quantitative definition of information. *Inform. Transmission* 1 (1965), 3-11, also *Int. J. Comp. Math.* 2 (1968), 157-168.
7. MARTIN-LÖF, P. The definition of random sequences. *Inform. and Contr.* 9 (1966), 602-619.
8. PAGER, D. On the problem of finding minimal programs for tables. *Inform. and Contr.* 14 (1969), 550-554.
9. BLUM, M. On the size of machines. *Inform. and Contr.* 11 (1967), 257-265.
10. PAGER, D. Further results on the problem of finding the shortest program for a decision table. Presented at Symposium on Computational Complexity, Oct. 25-26, 1971; abstracted in *SIGACT News*, no. 13 (Dec. 1971), p. 14.
11. PUTNAM, H. Trial and error predicates and the solution of a problem of Mostowski. *J. Symb. Logic* 30 (1965), 49-57.

RECEIVED OCTOBER 1972; REVISED JULY 1973